

SFP-120-GD

1000BASE, SFP, EZX, SMF TRANSCEIVER

1550nm, 120km REACH, DUPLEX LC CONNECTOR

Product Features

- Up to 155Mb/s Data Links
- Hot-Pluggable SFP
- Duplex LC connector
- Up to 120km on 9/125µm SMF
- 1550nm DFB laser transmitter
- Single +3.3V Power Supply
- Low power dissipation <1W typically
- Available operating temperature ranges:
 - Commercial: 0°C to 70°C
 - Industrial: -40°C to 85°C
- RoHS compliant and Lead Free



Product Applications

- 1000Base-EZX Ethernet
- FC

I. Maximum Ratings

Exceeding the limits below may damage the transceiver module permanently.

Parameter	Symbol	Min.	Typ.	Max.	Units
Storage Temperature	TS	-40		+85	°C
Power Supply Voltage	Vcc	-0.5		4	V
Relative Humidity	RH	0		85	%

II. Operating Specifications

Parameter		Symbol	Min.	Typ.	Max.	Units
Case Operating Temperature	Commercial	TC	0		+70	°C
	Industrial		-40		+85	°C
Supply Voltage		VCC	3.135		3.465	V
Supply Current		Icc			300	mA
Inrush Current		Isurge			Icc+30	mA
Maximum Power		Pmax			1	W

III. Optical Characteristics


Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes
Data Rate	BR		155		Mb/s	
Bit Error Rate	BER			10 ⁻¹²		
Max. Supported Link Length on 9/125µm SMF@1.25Gb/s	LMAX		120		km	
Total System Budget	LB	34			dB	
Transmitter						
Center Wavelength	λc	1530	1550	1570	nm	
Spectral Width	σ			1	nm	
Optical Output Power	Pout	0		5	dBm	1
Extinction Ratio	ER	10			dB	
Optical Rise/Fall Time	tr / tf			500	ps	2
Output Eye Mask	Compliant with IEEE802.3 z (class 1 laser safety)					
Receiver						
Optical Input Wavelength	λc	1260		1600	nm	
Receiver Overload	Pol	-10			dBm	3
RX Sensitivity	Sen			-34	dBm	3
RX_LOS Assert	LOS A	-45			dBm	
RX_LOS De-assert	LOS D			-35	dBm	
RX_LOS Hysteresis	LOS H	0.5			dB	

Notes:

1. The optical power is launched into SMF.
2. 20-80%.
3. Measured with PRBS 27-1 at 10-12 BER

SFP-120-GD

1000BASE, SFP, EZX, SMF TRANSCEIVER
1550nm, 120km REACH, DUPLEX LC CONNECTOR



IV. Electrical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes
Transmitter						
Input differential impedance	RIN	90	100	110		1
Single ended data input swing	Vin PP	250		1200	mVpp	
Transmit Disable Voltage	VD	Vcc-1.3		Vcc	V	2
Transmit Enable Voltage	VEN	Vee		Vee+0.8	V	
Transmit Disable Assert Time	Tdessert			10	us	
Receiver						
Single ended data output swing	Vout,pp	300		800	mV	3
Data Output Rise time	tr			500	ps	4
Data Output Fall time	tf			500	ps	4
LOS Fault	Vlosfault	Vcc-0.5		VCC_host	V	5
LOS Normal	Vlosnorm	Vee		Vee+0.5	V	5
Power Supply Rejection	PSR	100			mVpp	

Notes:

1. AC Coupled.
2. Or Open Circuit.
3. Into 100 ohm differential termination.
4. 20-80%
5. LOS is LVTTTL. Logic 0 indicates normal operation; logic 1 indicates no signal detected.

V. Ordering Information

Pivotal Part Number	Description
SFP-120-GD	SFP, 1550nm, EZX SMF 120km, 1000Base DDM, C-Temp
SFP-120-GDI	SFP, 1550nm, EZX SMF 120km, 1000Base DDM, I-Temp

Notes:

1. Please contact sales for specific OEM Platform part numbers to fit your network.

Warranty

<https://pivotaloptics.com/warranty/>

Disclaimer

External physical characteristics are subject to variation. This may include, but is not limited to, external case designs, pull tab colors and/or shapes, removal latch styles or colors, and label sizes and placement. These variations do not affect the function or characteristics of the transceivers.